



PL SELECT MD-3 ATF

Product Description:

PL SELECT MD-3 ATF is a general purpose automatic transmission fluid manufactured from premium quality base oils and blended with a specifically balanced additive combination to provide high oxidation stability, excellent foam resistance, corrosion and wear protection, and heat resistance. This complex fluid is also compounded with a friction-modifying additive to provide smooth lock-up of clutches without chatter.

PL SELECT MD-3 ATF is a general-purpose fluid that meets and exceeds all the old OEM specifications like MERCON, Allison and others.

Typical Uses:

- Meets the Performance requirements of **MERCON**
- Also meets the performance requirements of Chrysler, Allison C4 specifications.
- Recommended for all European OEM requirements.
- Recommended for **Use in all General Motors Vehicles**, where **DEXRON VI** product is **not** recommended

Features:

- Excellent wear protection and quiet, smooth operation.
- Superior thermal and oxidation stability.
- Protects against rust and corrosion.
- Outstanding seal compatibility.
- Dyed red to detect leaks.
- General Purpose fluid - Reduced inventory.

Typical Inspections

GRAVITY, ° API	33.0
FLASH POINT, ° C.	204
POUR POINT, ° C.	- 48
VISCOSITY:	
cP @ - 40° C. Brookfield	16500
cSt @ 40 ° C.	35.33
cSt @ 100° C.	7.16
VISCOSITY INDEX	171
COLOR, D-1500	Red

VALUES SHOWN HERE ARE TYPICAL AND MAY VARY